

polk

DB+

MARINE CERTIFIED
SUBWOOFER SERIES

POLKAUDIO.COM



polk

DB+



MARINE CERTIFIED

IP56 rating (water- and dirt-resistant)

Waterproof rubber surrounds keep the elements out

UV tolerant composite cone

Tested for salt-fog, UV and humidity

Polk's rich, deep bass gets an on-the-go overhaul with the marine-tough, yet ruggedly sophisticated, DB+ subwoofers. With a space-saving design you get thunderous sonic output that fits in nearly any vehicle.

Features

Rich Deep Bass, On the Go

Delivers thunderous sonic output and powerful low frequency response whenever... that will get your heart pumping.

Marine Certified

Built to last for cars, boats and ATVs with an IP56 rating and tested for Salt-fog, UV & Humidity.

Space Saving Design

Slimmed down form factor reduces the need for oversized subwoofer enclosures for a look that goes virtually unnoticed—but a sound that doesn't.

Dynamic Balance Technology

Patented process that guides material selection through rigorous testing that identifies and cancels out unwanted resonant frequencies.



DB+ Series Subwoofer Specifications

	DB 842 (SVC & DVC)	DB 1042 (SVC & DVC)	DB 1242 (SVC & DVC)
Type	8" Subwoofer	10" Subwoofer	12" Subwoofer
Driver Complement (inches & mm)	8" 203.2 mm	10" 254 mm	12" 304.8 mm
Cutout Dimensions (inches & mm)	7.28" 185 mm	9" 230 mm	11" 282 mm
Mounting Height (inches & mm)	0.51" 13.05 mm	0.52" 13.21 mm	0.51" 13.05 mm
Mounting Depth: Top (inches & mm)	3.82" 97 mm	4.34" 110 mm	4.34" 110 mm
Mounting Depth: Bottom (inches & mm)	4" 102 mm	4.56" 116 mm	4.56" 116 mm
Peak Power Handling	750 W	1050 W	1110 W
Continuous Power Handling	250 W	350 W	370 W
Nominal Impedance (ohm)	4	4	4
Frequency Response (Hz)	30Hz-200kHz	28Hz-200kHz	26Hz-200kHz
Sensitivity (dB)	84	85	86

VOLUME

SEALED ENCLOSURES

	Minimum Sealed	Maximum Sealed
DB 842 (SVC & DVC)	0.5 cu. ft.	1.2 cu. ft.
DB 1042 (SVC & DVC)	1.0 cu. ft.	2.4 cu. ft.
DB 1242 (SVC & DVC)	1.25 cu. ft.	3.5 cu. ft.

VOLUME

VENTED ENCLOSURES

	Minimum Sealed	Maximum Sealed
DB 842 (SVC & DVC)	0.66 cu. ft.	1.2 cu. ft.
DB 1042 (SVC & DVC)	1.25 cu. ft.	1.75 cu. ft.
DB 1242 (SVC & DVC)	1.75 cu. ft.	2.25 cu. ft.